



CRYSTIC[®] **ROOF**



REVIVE

Extending the life of your GRP roof

CrysticROOF® REVIVE



CrysticROOF® Revive will give any GRP roof a new lease of life. Without the need for a catalyst, CrysticROOF® Revive is a one component moisture curing polyurethane based waterproofing membrane which is designed as an overlay directly onto an existing GRP roof.

This is a heavy duty, fully aliphatic membrane that can easily be applied in **one coat without the need of a primer**. It can be applied directly as a GRP one coat refurbishment solution or applied wet on wet with a reinforcing fleece.

We recommend this product for waterproofing and protection of existing GRP roofs.

KEY BENEFITS

- **Fast**
Just one coat needed on a GRP roof (reinforcing fleece then an additional coat if needed)
- **One component**
You don't need to add hardeners or catalyst, no matter what season you're applying it in
- **No primer or catalyst on a GRP roof**
Unlike other products, you do not need to add a primer or catalyst on a grp roof. Other substrates may differ.
- **Easy repair**
No sanding or acetone cleaning before application
- **Cost effective**
Fast application and fewer coats means less material which in turn keeps costs down
- **UV stable**
Doesn't break down with exposure to UV and pollution
- **300% elasticity**
6 times more elastic than GRP and can be used over large roof areas
- **Weather resistance**
It's wide service temperature range means it stays secure in all weather



EASY POUR
CONTAINER

APPLICATION



REFURBISHMENT OF EXISTING GRP

1. Thoroughly clean the GRP with a pressure washer making sure any oil, grease or wax contaminants are removed as well as cement lattice, loose particles and mould. Any loose substrate should be removed and replaced.
2. Apply CrysticROOF® Repair sealant to any cracks, splits or blemishes. (Can be used with a reinforcing fleece if needed).
3. Apply a single coat of CrysticROOF® Revive to the entire substrate at a minimum consumption rate of 2kg/m².

CrysticROOF® REVIVE OVERVIEW

✓ Flexibility

More than 300%

✓ Ready to use

No requirement for the addition of additives or hardeners

✓ Fast application time

First coat, reinforcing fleece and a final coat

✓ Ease of repair

Can be patched quickly and easily

✓ Hardness

60 Shore D without the need for a topcoat

✓ Tensile strength

>20MPa

✓ Elongation

>300%

Prior to application ensure you read CrysticROOF® Revive Technical Data Sheet (TDS)
Minimum consumption: 2kg/m² (subject to substrate condition)

The information contained within this brochure was correct at time of print, but could be subject to change at any time. The installation guide and materials estimators are 'guides' and should be used in such a manner. If further details are required, please ask for advice prior to installation. **Other products in the range** – please ask for information before use. Y3441V50919

[crysticroof.com](https://www.crysticroof.com)



 **SCOTT BADER**
Making a **positive** difference